



Regulation No. 305/2011 DoP-Icon-Line Eclipse XL-2620-2022

1. Model identifier	Icon-Line Eclipse XL / Eclipse XL B / Eclipse XL S / Eclipse XL Low
Intended use or uses of the construction product, in accordance with the applicable technical specification	Room heater solid fuel, space heating in residential building
3. Name and contact address of the manufacturer	Heta A/S, Jupitervej 22, DK-7620 Lemvig. heta@heta.dk
System of assessment and verification of constancy of performance of the construction product	System 3
Notified body relevant to the assessment and verification of constancy of performance	Danish Technological Institute, DK-8000 Aarhus Notified body No. 1235. Report nr. 300-ELAB-2620-EN

6. Essential characteristics

Mechanical resistance and stability	20 kg Load bearing capacity				
Fire safety					
Minimum distance to combustible materials	Minimum distances in mm				
Bottom (dB) Ceiling (dC) Rear (dR) With insulation/without insulation Side (dS) Furniture in front (dP) Corner (45°) (dS!) Floor front (dF) Side radiation area (dL) Ceiling/ Mantel (dC!) Door to hearth (dB!)	0 (<65K) 750 75/ 125 400 1200 50 0 (550 Eclipse XL Low) 0 (<65K) 450/ 500 0 (<65K)				
Hygiene, health and the environment					
Emissions at nominal heat output (Harmonized technical specification EN 16510-2-1-2022)					
(≤) 1500 mg/m³ (≤) 200 mg/m³ (≤) 120 mg/m³ (≤) 40 mg/m³	Nox 94 mg/Nm³				

Safety and accessibility in use

Data for installation to a chimney at nominal heat output			
Flue gas outlet temperature	352 °C		
Minimum flue draught	11 Pa		
Flue gas mass flow	5,7 g/s		
Data for installation to a chimney regarding fire safety test heat output			
Fire safety of installation to the chimney	T400G		

Energy economy and heat retention

Appliance's thermal output and energy efficiency at nominal heat output			
Space heat output		7,1 kW	
Efficiency	≥ 75%	<i>η</i> 81%	
Seasonal space heating efficiency at appliance's nominal heat output	≥ 65%	η _s 71%	
Energy efficiency		EEI 107	
		Class A+	

7.

The performance of the product identified in points 1 and 2 is in conformity with the declared performance in point 8. This declaration of performance is issued under the sole responsibility of the manufacturer.

Signed on behalf the manufacturer of 04.09.2025

