Certifikat no. 1554

Declaration of Performance EN

Regulation No. 305/2011

DOP-Scan-Line 95-1554-2011

1. Model identifier	Scan-Line 95
2. Intended use or uses of the construction product, in accordance with the applicable technical specification	Room heater solid fuel, space heating in residential building
3. Name and contact address of the manufacturer	Heta A/S, Jupitervej 22, DK-7620 Lemvig. heta@heta.dk
4. System of assessment and verification of constancy of performance of the construction product	System 3
5. Notified body relevant to the assessment and verification of constancy of performance	Danish Technological Institute, DK-8000 Aarhus Notified body No. 1235. Report nr. 300-ELAB-1554-EN

6. Essential characteristics

Mechanical resistance and stability	20 kg Load bearing capacity
Fire safety	
Minimum distance to combustible materials	Minimum distances in mm
Bottom (dB) Ceiling (dC) Rear (dR) Side (dS) Furniture in front (dP) Corner (45°) (dS!) Floor front (dF) Side radiation area (dL) Ceiling/ Mantel (dC!) Door to hearth (dB!)	0 (<65K) 750 150/ 75 (isolated) 350 (Turnable 855) 1100 350 (Turnable: Scan-Line 95: (433)) 0 (<65K) 0 (<65K) NPD 350 (Lower than 350, the floor must comply EU standard for fire safety: A2-s1,d0)
Hygiene, health and the environment	
Emissions at nominal heat output (Harmonized technical specification EN 16510-2-1-2022)	

(≤) 1500 mg/m³	CO	1120 mg/Nm³
(≤) 200 mg/m³	Nox	106 mg/Nm³
(≤) 120 mg/m³	OGC	55 mgC/Nm³ at 13% O_2
(≤) 40 mg/m³	Particles	29 mg/Nm³

Safety and accessibility in use

Data for installation to a chimney at nominal heat output	
Flue gas outlet temperature	335 °C
Minimum flue draught	13 Pa
Flue gas mass flow	6,3 g/s
Data for installation to a chimney regarding fire safety test heat output	
Fire safety of installation to the chimney	T400G

Energy economy and heat retention

Appliance's thermal output and energy efficiency at nominal heat output		
Space heat output		7,2 kW
Efficiency	≥ 75%	η 80%
Seasonal space heating efficiency at appliance's nominal heat output	≥ 65%	η_s 70%
Energy efficiency		EEI 106
		Class A

7.

The performance of the product identified in points 1 and 2 is in conformity with the declared performance in point 8. This declaration of performance is issued under the sole responsibility of the manufacturer.

Signed on behalf the manufacturer of 06.06.2025

HETA
Jupitervej 22, DK-7620 Lemvig
TLF: +45 96 63 06 00
Martin Bach

In case of any change of the above-mentioned product, this Declaration of Performance becomes invalid.
Heta A/S, Jupitervej 22, DK-7620 Lemvig, Tlf. +45 9663 0600, www.hetaheating.com