



## Declaration of Performance GB



Regulation No. 305/2011  
DOP-Scan-Line Green 150 2589

|  |   |
|--|---|
| 1. Unique identification code of product-type  | pellet Stove  |
| 2. Product name  | Green 150 series  |
| 3. Intended use or uses of the construction product, in accordance with the applicable technical specification | Room heating appliance, fueled by pellets without hot water supply                                    |
| 4. Name and contact address of the manufacturer  | Heta A/S, Jupitervej 22, DK-7620 Lemvig. heta@heta.dk   |
| 5. Where applicable, name and contact address of authorized representative. E-mail.                            | Martin Bach, E-mail: martin.bach@heta.dk  |
| 6. System of assessment and verification of constancy of performance of the construction product               | System 3  |
| 7. Notified body relevant to the assessment and verification of constancy of performance                       | Danish Technological Institute, DK-8000 Aarhus<br>Notified body No. 1235. Report nr. 300-ELAB-2589-EN |

### 8. Declared Performance

| Harmonized technical specification | EN 14785:2006 Nominal output   | EN 14785:2006 Low output   |
|------------------------------------|--|--|
| Emission                           | CO 0,006%/73 mg/m <sup>3</sup> <sub>n</sub><br>Nox 181 mg/m <sup>3</sup> <sub>n</sub><br>Dust 15 mg/m <sup>3</sup> <sub>n</sub><br>Dust (NS3058/3059) --- g/kg<br>OGC (CEN/TS 15883) 4 mgC/m <sup>3</sup> <sub>n</sub> ved 13% O <sub>2</sub><br>Energy consumption 66 W/h | CO 0,023%/288 mg/m <sup>3</sup> <sub>n</sub><br>Nox 184 mg/m <sup>3</sup> <sub>n</sub><br>Dust 18 mg/m <sup>3</sup> <sub>n</sub><br>Dust (NS3058/3059) --- g/kg<br>OGC (CEN/TS 15883) 18 mgC/m <sup>3</sup> <sub>n</sub> ved 13% O <sub>2</sub><br>Energy consumption 44 W/h |

### Fire safety

|  |                         |
|--|-------------------------|
| Reaction to fire   | A1                      |
| Test of fire safety in connection with the burning of wood | Approved                |
| Distance to combustible materials                          | Minimum distances in mm |
| Rear   | 60                      |
| Sides distance to combustible materials                    | 90                      |
| Distance to floor from lower edge of the door              | ---                     |
| Furniture distance   | 770                     |

### Safety

|   |                  |
|---|------------------|
| Mechanical resistance (to carry a chimney / flue) | Not tested (NPD) |
| Electrical safety                                 | Pass             |
| Surface temperature                               | Pass             |
| Cleanability                                      | Pass             |

### Thermal output

|  |             |
|--|-------------|
| Nominal heat output                        | 3,6-7,3 kW  |
| Room heat output                           | 3,6-7,3 kW  |
| Energy efficiency                          | η 96%-94%   |
| Fluegas temperature at nominal heat output | T 55°C-87°C |
| Water heating output                       | NA (NPD)    |
| Maximum water operating pressure           | NA (NPD)    |

### 9.

The performance of the product identified in points 1 and 2 is in conformity with the declared performance in point 8. This declaration of performance is issued under the sole responsibility of the manufacturer.

Signed on behalf the manufacturer of 05-01-2023

**Heta A/s**

JUPITERVEJ 22 - DK-7620 LEMVIG  
Tlf. +45 9663 0600 FAX +45 9663 0616  
Martin Bach

After the 05-01-2023 change of the above-mentioned production type this Declaration of Performance becomes invalid.

Heta A/S, Jupitervej 22, DK-7620 Lemvig, Tlf. +45 9663 0600, www.heta.dk